

Features

- Dual compartments with individual temperature control.
- Three stage battery protection system prevents vehicle run out of battery.
- Car & home dual use (DC/AC).
- Battery compartment for optional detachable battery.
- Shockproof and durable design for handling rocky road.
- Wire storage baskets, interior drain plug and LED light.
- Digital display control panel and smart phone APP control for operation easily.
- Reliable sealing technique, good insulation foam.
- Reverse/removable fridge door design.
- Safe to run less than a 45-degree angle in short time.
- Quiet operation: Less than 45db, like living in quiet suburb.

MODEL:	SECTW75	SECTW95
TOTAL CAPACITY:	72L/76Quarts/2.54cu. Ft.	90.2L/95Quarts/3.18cu. Ft.
COMPARTMENT 1 (FRIDGE/FREEZER)	27.5L/29Quarts/0.97cu. Ft.	35.6L/37Quarts/1.25cu. Ft.
COMPARTMENT 2 (FRIDGE/FREEZER)	44.SL/47Quarts/1.57cu.Ft.	54.6L/58Quarts/1.93Cu.Ft
POWER SUPPLY:	12/24V DC,100-240V AC	12/24V DC,100-240V AC
FRIDGE DIMENSION (WX D X H):	873*492*465mm 34 3/8 *19 3/8 *18 1/4 inch	943*528*465mm 37 1/8*20 3/4 *18 1/4 inch
PACKING SIZE (WXDXH):	908*576*524mm 35 3/4 *22 11/16 *20 5/8inch	978*612*524mm 38 1/2*24 1/4 *20 5/8inch
NET WEIGHT:	23.5kg/51.81lbs	24.8kg/54.67lbs
GROSS WEIGHT:	27.0kg/59.Slbs	28.4kg/62.61lbs
FRIDGE/FREEZER (COMBINATION):	-20~20°C(-4~68°F)	-20~20°C(-4~68°F)
FCL QUANTITY:	88/184/184 (20'40'40'HQ)	80/172/172 (20'40'40'HQ)
RATED CURRENT:	DC 6.0A/3.0A AC I.5A-0.7A	DC 6.0A/3.0A AC 1.SA-0. 7 A
RATED POWER INPUT:	80W	80W
NOISE LEVEL:	<45dB	<45dB
*Due to product improvement, the technical information might be different from actual information, please refer to the rating label on the product. (Note:±3°C temperature difference is permitted)		




Door latch



Digital display



Heavy duty handle



Interior LED light& Drain plug



Car/home /Solar(Optional)



Detachable battery(Optional)



Reverse/removable door



Protective foot pad